

Product Information

Monomeric 100µ thick white gloss PVC with grey-coloured removable adhesive, laminated on a two-sided PE-coated silicone paper liner.

The PVC offers an excellent dimensional stability and a good opacity.

Exceptional print quality with solvent, eco-solvent and UV inks.

PE release liner ensures media lays flat during and after printing.

Particularly suitable for all short-term removable signage on flat surfaces such as real estate signage, billboards, commercial advertising boards and removable window graphics with exceptional removability from most surfaces.

Also suitable for blackout applications.

Shelf Life

1 year when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Recommendations for Laminating

Please ensure the print is perfectly dry before laminating. We suggest to let the material dry for at least 48 hours after printing.

Recommended Overlaminates Film

Neolam NL20 Gloss Transparent Overlaminates

Technical Data

Carrier:	monomeric PVC, highly stabilised, calendared
Thickness:	100 µ +/- 5%
Gloss Level:	60%
Adhesive:	grey-coloured adhesive dispersion removable
Initial Adhesion:	N/25mm >/= 3
24h, 180° Peel:	N/25mm >/= 5
Liner:	two-sided PE-coated silicone paper (140 gsm)
Dimensional Stability MD:	</= 1.5mm
Dimensional Stability CD:	</= 1.0mm
Tensile Strength MD:	N/25mm >/= 45
Tensile Strength CD:	N/25mm >/= 35
Production temperature:	25°C +/- 5°C relative humidity of 50 +/- 10%
Application temperature:	20°C +/- 10°C relative humidity of 50 +/- 10%
Outdoor durability:	2 years (unprinted film)

Standard Dimensions

1370mm X 50M