

# **Product Information**

PVC/PET (white satin, 300µ)

A durable synthetic grade with short drying time, brilliant colour reproduction, high opacity and sharp print definition.

Provides perfect waterproof qualities and excellent non-curl properties.

Special surface treatment for low static and precise ink adhesion.

Unique blockout characteristics so light does not penetrate through the reverse side of your print.

Designed specifically for solvent, eco-solvent, and UV printers.

Particularly suitable for retractable banner stands, POS displays, posters and displays where non-curling film is required.

## **Shelf Life**

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

# **Technical Data**

PVC/PET
300µ +/- 10%
420 gsm
0.75
matt
very good
N/A
N/A
MD: $\geq$ 140MPa / TD: $\geq$ 30Mpa
MD: $\geq$ 135MPa / TD: $\geq$ 20Mpa
$MD{:}{\geq}5\% \ / \ TD{:}{\geq}2\%$
+10 - +40°C
-20 - +50°C
L:66.39 a:1.48 b:0.59
37.94/-1.45

## **Standard Dimensions**

915mm X 50M 1270mm X 50M 1600mm X 50M 2000mm X 50M

#### **Standard Core**

3 inch

#### © NEOPRINT™ 2015

No part of this publication may be copied, scanned or reproduced in whole or part in any form without written permission from NEOPRINT<sup>TM</sup>.

NEOPRINT<sup>™</sup> products are warranted to be free from defects in workmanship or materials. Technical data is based on information we believe to be reliable; however, such information does not constitute a warranty. The purchaser should carefully consider the suitability of NEOPRINT<sup>™</sup> for each intended use and the purchaser shall assume all risks regarding each use. The seller shall not be liable for damages in excess of the sale price of the products nor for incidental or consequential damages. All technical data is subject to change without notice.