

Product Information

Neotape NT100 General Purpose Medium Tack Application Tape is based on a special impregnated paper with low tensile elongation and high wet strength.

Suitable for transferring self adhesive letters produced from cast and calendered PVC colored films according to CAD/CAM techniques.

Especially to be emphasised are the following properties:

- The natural rubber adhesive guarantees an excellent adhesion on PVC films because of the relatively high coating weight.
- The impregnated carrier paper shows an excellent stability of shape, with no curl even under moist conditions.
- Based on the tape translucence, the alignment – even of small letterings and logos – is simplified.
- Neotape NT100 Application Tape can be rewound easily from the roll.

Shelf Life

1 year when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Technical Data

| | |
|------------------|----------------------------|
| Carrier: | Special paper, impregnated |
| Adhesive: | Natural rubber |
| Adhesion [N/cm]: | 2,20 +/- 10 % |
| Thickness [mm]: | 0,10 +/- 5 % |

Standard Dimensions

1220mm X 91.4M

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals.

This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product.

The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request.

This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.