

Product Information

Neoflex I-JET Premium 510 Satin Single Side Banner is a UV resistant, 510gsm, PVC coated, smooth satin surfaced reinforced banner vinyl exhibiting a scrimless appearance after printing.

It is ideal for closely viewed, high resolution images used in high strength indoor or outdoor sign and banner applications.

I-JET's softer coating has a more supple and flexible feel and is dimensionally stable, welds well and is visually appealing.

I-JET is anti-static, UV stabilised and fire retardant. It is ideal for use in high strength indoor or outdoor sign and banner applications.

Features

Frontlit, excellent layflat, smooth surface, high resolution print quality with low curl properties.

Suitable for most solvent, UV curable digital and screen printing.

Shelf Life

12 months from manufacture date, when stored in the original packaging between 22°C and 50°C at 55% relative humidity.

Technical Data

Composition:	high tensile woven polyester yarn knife coated with PVC resin
Weight:	510gsm +/- 5%
Thickness:	0.43mm +/- 5%
Yarn:	1100 x 1100 Denier
Surface tension:	42 Dyne/cm ³
Welding adhesion:	8.0kg/50mm
Coating adhesion:	142.1 N/50mm
Flame retardant:	NFPA-701 DIN4102-B1
Environmental:	EN-71 RoHS
Tensile strength md:	239 kg/50mm
Tensile strength cd:	216 kg/50mm
Elongation at break md:	25.3%
Elongation at break cd:	27
Service temperature:	-30°C to 70°C

Standard Dimensions

1370mm X 50M
1600mm X 50M
2500mm X 50M
3200mm X 50M