



NL20 Transparent Gloss Overlamine Film

Product Information

Neolam NL20 Transparent Gloss Overlamine is a monomeric 100µ, transparent, gloss PVC film for protecting digitally printed images.

NL20 has permanent ultra-clear adhesive and contains UV absorbers, it delivers increased image brightness and extends durability of laminated prints.

A PE "layflat" release liner ensures ease of use in all application situations.

Suitable for all short term overlamine applications such as real estate signage and short term promotions signage and advertising.

Recommendations for Laminating

Please ensure the print is perfectly dry before laminating. It is recommended to allow printed material to dry for at least 48 hours after printing, prior to laminating.

Recommended Overlamine for:

Neoprint NP2000 Series Digital Vinyl

Technical Data

Construction:	Monomeric PVC
Thickness:	100µ
Adhesive:	permanent ultra-clear pressure sensitive with UV absorbers solvent based acrylic
Liner:	two-sided PE-coated paper
Laminating:	cold or heat assist
Service temperature:	-25°C to 82°C
Application temperature:	≥10°C (18 to 25°C optimum)
Durability:	2 years
Shelf Life:	1 Year when stored in original packaging between 20°C and 25°C at 50% relative humidity.

Standard Dimensions

1370mm X 50M

© NEOPRINT™ 2018

No part of this publication may be copied, scanned or reproduced in whole or part in any form without written permission from NEOPRINT™.

NEOPRINT™ products are warranted to be free from defects in workmanship or materials. Technical data is based on information we believe to be reliable; however, such information does not constitute a warranty. The purchaser should carefully consider the suitability of NEOPRINT™ for each intended use and the purchaser shall assume all risks regarding each use. The seller shall not be liable for damages in excess of the sale price of the products nor for incidental or consequential damages. All technical data is subject to change without notice.