



## Neoprint NFPBL-G Gloss Frontprint Backlit Polyester Film

### Product Information

Neoprint Gloss Frontprint Backlit Polyester Film is a 210 micron, polyester film with a semi-transparent, gloss finish.

Advanced ink adhesion achieves excellent colour reproduction and saturation deliver exceptional print quality with solvent, eco-solvent, latex and UV inks.

NFPBL-G is highly resistant to heat and does not buckle making it ideal for all illuminated lightbox, display and point of sale graphics.

### Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

### Technical Data

|                          |               |
|--------------------------|---------------|
| Base materials:          | PET           |
| Finish:                  | gloss         |
| Weight:                  | 210µ +/- 10%  |
| Specific gravity:        | 0.75          |
| Ink application:         | high coverage |
| Application temperature: | +10 to +60°C  |
| Service temperature:     | -20 to +90°C  |

### Standard Dimensions

1270mm X 30M  
1525mm X 30M

#### © NEOPRINT™ 2018

No part of this publication may be copied, scanned or reproduced in whole or part in any form without written permission from NEOPRINT™.

NEOPRINT™ products are warranted to be free from defects in workmanship or materials. Technical data is based on information we believe to be reliable; however, such information does not constitute a warranty. The purchaser should carefully consider the suitability of NEOPRINT™ for each intended use and the purchaser shall assume all risks regarding each use. The seller shall not be liable for damages in excess of the sale price of the products nor for incidental or consequential damages. All technical data is subject to change without notice.