

Product Information

PVC/PET (white lightly textured, matt, 300 μ)

A durable synthetic grade with short drying time, brilliant colour reproduction, high opacity and sharp print definition.

Provides perfect waterproof qualities and excellent non-curl properties. High resistance to the effects of heat during the printing process.

Special surface treatment for low static and precise ink adhesion.

Unique blockout characteristics so light does not penetrate through the reverse side of your print.

Designed specifically for use on Latex printers, also suitable for printing with solvent, eco-solvent and UV inks (not suitable for waterbased pigment).

Particularly suitable for retractable banner stands, POS displays, posters and displays where non-curling film is required.

Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Technical Data

Base materials:	PVC/PET
Thickness:	300 μ +/- 10%
Weight:	420 gsm
Specific gravity:	0.75
Surface:	lightly textured, matt, white
Surface brightness:	6.5GS approx (ZC/QR08 - D60)
Ink application:	excellent ink coverage, fast drying times
Tensile strength:	MD: \geq 140MPa / TD: \geq 30Mpa
Tear strength:	MD: \geq 135MPa / TD: \geq 20Mpa
Elongation at break:	MD: \geq 5% / TD: \geq 2%
Application temperature:	+5°C to +45°C
Service temperature:	-20°C to +50°C
Durability:	Indoor use up to 1 year

Standard Dimensions

915mm X 50M
1270mm X 50M

Standard Core

3 inch